Remote Cargo Hook Test Form
C2

DART AEROSPACE

MAKE SURE YOU ARE USING THE CORRECT TEST FORM FOR THE CORRECT SOLENOID!   NEW SOLENOID (152951-001)

Work Order: _____   Customer: _____

Serial Number: _____   Date: _____

# of Releases	Load (Lbs.)	Release Method	Remarks	Result	Pass/fail
1	5,000	Static Hold	Hold for two Minutes and reduce load to zero	N/A	
10	1,000	Electircal, 25 volts	No "hang ups" permitted	N/A	
2	2,000	Electircal, 22 volts	Current shall not exceed 13.0A	Amp.	
2	1,500	Electircal, 22 volts	Current shall not exceed 13.0A	Amp.	
2	1,000	Electircal, 22 volts	Current shall not exceed 13.0A	Amp.	
2	500	Electircal, 22 volts	Current shall not exceed 13.0A	Amp.	
2	100	Electircal, 22 volts	Current shall not exceed 13.0A	Amp.	
1	2,000	Electircal, 20 volts	Current shall not exceed 13.0A	Amp.	
1	2,000	Electircal, 28 volts	Current shall not exceed 13.0A	Amp.	
1	2,000	Manual		N/A	
1	2,000	Impact Test	Impact shackle 10 times, shall not release	N/A	
1	N/A	Solenoid Ohms	Shall not exceed 2.1 - 2.4 Ohms	Ohms	
1	N/A	Electircal Continuity	Across both wires	N/A	

Test Conducted By: _____   Signature _____